

Dromex



FIBRE LITE SNEAKERS



DF-FLITE-L

Description

The Dromex® Ladies Fibre Lite is a metal-free lightweight, stylish and sporty design safety shoe, which protects the users feet from mechanical hazards while offering optimum comfort for daily use. These shoes are suitable for use as a general protective safety shoe, used in warehouses, general industrial environments, freight and engineering industries.

The Fibre Lite range features the following

- Available in both mens (DF-FLITE-M) and ladies' option (DF-FLITE-L)
- S1PL classification (S1 - energy absorption of seat region, antistatic and perforation midsole).
- A lightweight yet impressive impact resistant fiberglass toecap rated up to 200 ± 4 Joules along with a lightweight Kevlar perforation midsole providing protection from penetrating objects and heat.
- An oil and slip resistant rated outsole, SR (Slip resistance on a ceramic tile floor with glycerine).
- A durable lightweight EVA rubber outsole with ESD technology and an insole with antistatic properties reduces the chance of electrostatic discharge.
- Heat insulation properties on the outsole up to 120° C ideal for use when working in the hot sun or in jobs where drastic temperature changes are frequent.
- The outsole has an energy absorption heel for comfort.
- A removable foam insock with antistatic thread, designed for comfort and easy cleaning
- Bellows tongue prevents liquids and particulates from penetrating through the shoes
- An oxford mesh upper for breathability and durability with PU (Polyurethane) leather and TPR (Thermoplastic rubber) accents.
- A synthetic inner lining, suitable for those who are allergic to chrome
- The upper features a reinforced nuback heel and TPU toe bumper for added protection and ease of removal.
- The cleated outsoles grip well for easy walk on terrain.

As these shoes have antistatic properties, they protect workers, sensitive equipment and components from electrostatic discharges present in general manufacturing industries, refineries, computer equipment manufacturing, medical industry and many other environments.

Special Instructions

- All safety protective footwear should be thoroughly inspected before use to ensure no damage is present.
- Should any damage be present such as distinct or deep cracks in the outsole, cracked or torn seams, material abrasions, tears on the upper parts, burns, upper has been separated from the outer sole or exposed toecap, the footwear must be replaced immediately.
- Should safety shoes be damaged during use, suitable protection is not guaranteed and must be replaced immediately.
- None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer.
- Safety footwear shall not adversely affect the health or hygiene of the user. Safety footwear shall be made of materials such as textiles, leather, rubbers or plastics that have been shown to be chemically suitable. The materials shall not, in the foreseeable conditions of normal use, release or degrade to release substances generally known to be toxic, carcinogenic, mutagenic, allergenic, toxic to reproduction or otherwise harmful.
- The manufacturer is examined under the system for ensuring quality of production by means of monitoring and inspection.
- These safety shoes are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment.
- Do not use these shoes near a fire or open flame.
- The information contained herein is intended to assist the wearer in the selection of personal protective equipment.
- Actual conditions of use cannot be directly simulated in a test environment; therefore, it is the responsibility of the end user and not the manufacturer or supplier to determine the footwear's suitability for the intended use.
- It is important to note that footwear is subject to many different conditions encountered in everyday use and that it is impossible to make footwear resistant to slip in all conditions. Nevertheless, it is generally accepted that problems are minimized if the guideline coefficients of friction is achieved.
- If the footwear is cared for and worn in the correct working environment and stored in dry ventilated conditions, it should give a good wear life, without premature failure of the outsole, upper and upper stitching.

Compliance & Conformity

Complies with the requirements of CE type examinations, EN ISO 20345:2022 that specifies basic and additional (optional) requirements for safety footwear used for general purpose. It includes, for example, mechanical risks, slip resistance, thermal risks, ergonomic behaviour. It also specifies requirements for safety footwear equipped with customized insocks, customized safety footwear or individual manufactured customized safety footwear.

NRCS Homologated approval number: NRCS/9002/217251/0629 as per SANS 20345:2023.

Specifications

Style:	Class 1, fabric upper, safety shoe with lace fasteners, a fibre glass toecap and kevlar midsole.	
Materials:	Toecap:	Fiberglass impact resistant up to 200J ± 4J
	Outsole:	Rubber with EVA (Ethylene-Vinyl Acetate) white colour midsole

Penetration resistant insert:	Kevlar
Upper:	Fly knit nylon
Insole:	Antistatic non woven material
Full removable insock:	HI-POLY foam

Sizes Available

2 - 9



UK SIZE	2	3	4	5	6	7	8	9
US SIZE	3	4	5	6	7	8	9	10
EU SIZE	36	37	38	39	40	41	42	43

Shelf life

- When stored in normal conditions (temperature, and relative humidity), footwear will perform as intended.
- As PU becomes brittle, wear the shoes regularly to maintain flexibility and support the lifespan of this shoe.
- Durability/expiration date:
These shoes are marked with the date of manufacture. Due to the large number of influencing factors, it is in general not possible to specify an expiry date. As a rough guideline, one can estimate they will last for at least 3 years from the date of production. The expiration period in addition depends on the degree of wear, how much they are used, what they are used for, and external factors such as heat, cold, moisture, UV radiation or chemical substances. This information applies to new, packaged shoes that are stored under conditions that are appropriate for the product, i.e., not subject to excessive temperature fluctuations or relative humidity.

Packaging, Storage & Obsolescence

- Dromex Fibre Lite Safety shoes are packed as individual pairs in a box.
- Store in a cool dry place away from sunlight.
- If the footwear becomes damaged, it will not continue to give the specified level of protection nor ensure that the wearer continues to receive the maximum protection. The footwear should be replaced immediately.
- The packaging provided with the footwear at the point of sale is to ensure that the footwear is delivered to the customer in the same condition as when dispatched. The packaging box can also be used for storing the footwear when not in use.
- When the boxed footwear is in storage, do not place heavy objects on top of it as this could cause breakdown of the packaging and possible damage to the footwear.



Cleaning & Maintenance

- All safety protective footwear should be thoroughly inspected before use to ensure no damage is present.
- After each use, brush and wipe dirt and mud of shoes with a damp (not wet) cloth and a mild soap.

Dromex: Cornubia Ridge Logistics Park, 30 Umganu Road, Flanders, Blackburn, Durban, South Africa, 4319
T. +27(31) 713 1960 E. info@dromex.co.za www.dromex.co.za

Manufactured by: Ningbo Fastest Safety, Production Products Co., Ltd
 RM 803, No. 456 Middle Taikang Road, Yinzhou, Zhejiang, P. R. China

Disclaimer

Dromex reserves the right to make changes without further notice to any products herein to improve function, design or reliability and validity. Dromex does not assume any liability arising out of the application or use of any product described herein. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

Latest update: 23/10/2024

- Do not use chemical products such as thinners, alcohol or other aggressive cleaning products as they can damage the material on the footwear by causing weak points, which is not visible to the users eye.
- Allow shoes to air dry at room temperature thoroughly between uses.
- Do not dry shoes on or near a heat source.
- Dry your shoes carefully when wet and avoid abrupt temperature changes.
- Safety shoes should not be left in contaminated condition if re-use is intended especially if potential hazards exist.
- Due to a wide variety of possible constructions and combinations with other materials we recommend to always consult your professional cleaning service to determine the best suitable cleaning method.

Testing Before Use

As these shoes contain solid parts, it is necessary to determine the appropriate size through careful testing and measuring. Before use, check the shoes for apparent defects. If you see signs of wear, the shoes should be replaced. Occasionally check the inside of the shoe by hand for damage to the lining and for sharp edges at the toe box, either of which may cause injury. Mounting system (zips, laces, rings) must be operable. Shoe closures must be properly used and laces must be tight.

- It is essential to determine the correct footwear size through testing of the footwear.
- Do not wear footwear worn by another person as footwear adapts to the wearers feet through frequent use.
- Always try on new footwear at midday or in the afternoon for the correct and best fit as feet normally swell during the day, especially if the users job entails standing.
- Walk in the new footwear to ensure it is comfortable and adapts to the users feet.
- Shoes should have ample room (toes should be about 12.5mm from the front).
- Do not expect footwear to stretch with wear.
- Make allowances for extra socks or special arch supports when buying safety footwear and confirm with the manufacturer if adding inserts affects your level of protection.
- Safety footwear should fit snugly around the heel and ankle when laced.
- Lace up shoes fully during fitting to avoid any tripping hazards or damage.


Donning and Doffing

- Ensure your feet and socks are completely dry before insertion into your shoes.
- Use a clean pair of socks each day as this helps to prevent odour and other hygiene issues.
- Before putting your safety shoe on, check that the position of the insock is in place within the shoe.
- Make sure the insock doesn't shift from its position. If it does, simply adjust it to the correct position.
- Unfasten the laces on your shoes.
- Carefully insert your foot into the shoe, using the pull tag as a support to push your foot in. Take care not to shift or move the insock out of place. If the insock moves, remove your foot and reposition it as before.
- Move your foot forward into the toecap area. Ensure the proper position: not too far forward as to push against the toecap and not too far as to leave a large space.
- Tighten the laces as required. The shoe should not feel too tight or loose.
- Test the fit and comfort of the shoe. Comfortable safety shoes are safer and will make the users experience more productive.
- If the shoe feels uncomfortable, is causing pain, and/or damaged, do not wear it.
- Unfasten the laces and pull your feet out of the shoe while holding the pull tag as a support.

Marking

Marking on footwear denotes that the footwear is licensed according to the PPE Directive and is as follows:

- Ladies Fibre Lite sneaker drawing:



- A Fiberglass Toecap
- B Black Mesh
- C Kevlar
- D Black non-woven fabric
- E Pink Mesh
- F White EVA Middle Sole
- G Rubber Outsole
- H White Mesh
- I Grey Split Nubuck Leather



- J Grey Split Nubuck Leather
- K Black TPU
- L Grey Oxford Cloth
- M Grey TPU
- N Black Non Metal Eyelet

- Swing Tag:

①



②



③



- Inner tongue:



- Insock:



- Outsole Embossing:



References:

ISO 20345: 2022

Standard

This safety footwear complies with the Regulation (EU) 2016/425 of 9 March 2016 on personal protective equipment and meets the requirements of the European standard EN ISO 20345:2022.

Safety footwear is manufactured using both synthetic and natural materials which conforms to the relevant sections of EN ISO 20345:2022 for performance and quality.

Safety Footwear is designed to minimise the risk of injury which could be inflicted by the wearer during use. It is designed to be used in conjunction with a safe working environment and will not completely prevent injury if an accident occurs which exceeds the testing limits of EN ISO 20345:2022.

Dromex: Cornubia Ridge Logistics Park, 30 Umganu Road, Flanders, Blackburn, Durban, South Africa, 4319
T. +27(31) 713 1960 E. info@dromex.co.za www.dromex.co.za
 Manufactured by: Ningbo Fastest Safety, Production Products Co., Ltd
 RM 803, No. 456 Middle Taikang Road, Yinzhou, Zhejiang, P. R. China

Disclaimer

Dromex reserves the right to make changes without further notice to any products herein to improve function, design or reliability and validity. Dromex does not assume any liability arising out of the application or use of any product described herein. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

Latest update: 23/10/2024

Toecaps

Dromex® Fibre Lite protective shoes are fitted with toecaps.

Toecaps protect the wearer's toes against the risk of injury from falling objects and crushing when worn in industrial and commercial environments, where potential hazards occur with the following protection plus, where applicable, additional protection: Impact protection is 200 Joules, Compression protection provided is 15,000 Newton's.

Additional Requirements for Special Applications

Additional protection may be provided and this is identified on the product by its marking as follows:

PROTECTION SYMBOL	EN ISO 20345:2022														Requirements	
	SB	S1	S2	S3	S3L	S3S	S4	S5	S5L	S5S	S6	S7	S7L	S7S		
	Closed heel area	O	X	X	X	X	X	X	X	X	X	X	X	X	X	Closed heel area
	200J resistant toe cap	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
	Toe protection cap with a compressive force of 15 kN	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
A	Antistatic shoes	O	X	X	X	X	X	X	X	X	X	X	X	X	X	Electrical resistance >100kΩ and ≤1000MΩ
E	Energy absorption of the heel	O	X	X	X	X	X	X	X	X	X	X	X	X	X	Absorbed energy ≤20J
FO	Hydrocarbon resistant sole	O	O	O	O	O	O	O	O	O	O	O	O	O	O	Volume increase 12%
WPA	Water penetration and water absorption of the outer material	O	-	X	X	X	-	-	-	-	X	X	X	X	X	Absorption ≤ 30% Penetration ≤ 0.2g
P	Puncture resistance (with a metallic, puncture-resistant midsole)	O	O	-	X	-	-	-	X	-	-	-	X	-	-	≤1100N
PL	Puncture resistance (with a PL-type non-metallic, puncture-resistant midsole)	O	O	-	-	X	-	-	-	X	-	-	-	X	-	at 1100N no perforation
PS	Puncture resistance (with a PS-type non-metallic, puncture-resistant midsole)	O	O	-	-	-	X	-	-	-	X	-	-	-	X	Average drilling force ≤ 1100N Single drilling ≤950N
CI	Cold insulation	O	O	O	O	O	O	O	O	O	O	O	O	O	O	Temperature drop after 30 min. at -17°C ≤ 10°C
HI	Thermal insulation	O	O	O	O	O	O	O	O	O	O	O	O	O	O	Temperature rise after 30 min. at 150°C ≤ 22°C
C	Conductivity	O	-	-	-	-	-	-	-	-	-	-	-	-	-	Electrical resistance ≤100kΩ
HRO	Heat resistance of the sole on contact	O	O	O	O	O	O	O	O	O	O	O	O	O	O	No signs of melting and/or fractures
M	Protection of the metatarsal bone	O	O	O	O	O	O	O	O	O	O	O	O	O	O	Residual height after impact: size 36 & below 37.0mm size 37 & 38 ≤ 38.0mm size 39 & 40 ≤ 39.0mm size 41 & 42 ≤ 40.0mm size 43 & 44 ≤ 40.5mm size 45 & above ≤ 41.0mm
CR	Cut resistant upper	O	O	-	O	O	-	O	O	O	-	O	O	O	O	Shear Strength Index 2.5
SR	Slip resistance (with glycerine-coated ceramic plate)	O	O	O	O	O	O	O	O	O	O	O	O	O	O	≤0.19 (forward sliding of the heel) ≤0.22 (backward sliding of the front part)
LG	Footwear suitable for ladders	O	O	O	O	O	O	O	O	O	O	O	O	O	O	Abrasion resistance of the outside dimensions suitable for use on ladders
SC	Abrasion resistance of the overcap	O	O	O	O	O	O	O	O	O	O	O	O	O	O	No through holes after 8000 abrasion cycles

X – Denotes a mandatory requirement. O – Denotes an optional requirement.

It is important that the footwear selected for use must be suitable for the protection required and wear environment.

Where a wear environment is not known, it is very important that consultation is carried out between the seller and the purchaser to ensure, where possible, the correct footwear is provided.

Slip Resistance Requirement

This footwear has been successfully tested against the EN ISO 20344:2021, clause 5.14 and the following symbol of SR applies.

Footwear resistant to slip on a ceramic tile floor with NaLS shall fulfil the requirements.

Test conditions	Coefficient of friction
Condition A (forward heel slip)	≥0.31

Test conditions	Coefficient of friction
Condition B (backward forepart slip)	≥0.36

Marking categories of safety footwear

Category	Basic Requirements (Table 2 and Table 3)	Additional requirements
SB	Class I or II	
S1	Class I	as SB, plus Closed heel area Energy absorption of seat region Antistatic
S2	Class I	as S1, plus Water penetration and absorption
S3 (metal insert type P) or S3L (non-metal insert type PL) or S3S (non-metal insert type PS)	Class I	as S2, plus: Perforation resistance according to the type Cleated outsole

Insock

This footwear is supplied with a removable insock. Please note that testing was carried out with the insock in place. This footwear shall only be used with the insock in place. The insock shall only be replaced by a comparable insock from the supplier to keep the protective properties of the footwear. Safety shoes and work shoes, which need to be modified orthopaedically, may only be modified with insock and materials which are certified by the manufacturer. Please ask the manufacturer to check this possibility.

For shoes that comply with the DGUV Rule 112-191, the insoles can additionally be replaced by the tested orthopaedic insoles.

Antistatic footwear

“Antistatic footwear should be used if it is necessary to minimize electrostatic build-up by dissipating electrostatic charges, thus avoiding the risk of spark ignition of, for example, flammable substances and vapours, and if the risk of electric shock from mains voltage equipment cannot be completely eliminated from the workplace. Antistatic footwear introduces a resistance between the foot and ground but may not offer complete protection. Antistatic footwear is not suitable for work on live electrical installations. It should be noted, however, that antistatic footwear cannot guarantee adequate protection against electric shock from a static discharge as it only introduces a resistance between foot and floor. If the risk of static discharge electric shock, has not been completely eliminated, additional measures to avoid this risk are essential. Such measures, as well as the additional tests mentioned below, should be a routine part of the accident prevention programme at the workplace.

Antistatic footwear will not provide protection against electric shock from AC or DC voltages. If the risk of being exposed to any AC or DC voltage exists, then electrical insulating footwear shall be used to protect from against serious injury.

The electrical resistance of antistatic footwear can be changed significantly by flexing, contamination or moisture. This footwear might not perform its intended function if worn in wet conditions.

Class I footwear can absorb moisture and can become conductive if worn for prolonged periods in moist and wet conditions. Class II footwear is resistant to moist and wet conditions and should be used if the risk of exposure exists.

If the footwear is worn in conditions where the soling material becomes contaminated, wearers should always check the antistatic properties of the footwear before entering a hazard area.

Where antistatic footwear is in use, the resistance of the flooring should be such that it does not invalidate the protection provided by the footwear.”

It is recommended to use an antistatic sock.

“It is, therefore, necessary to ensure, that the combination of the footwear its wearers and their environment is capable, to fulfil the designed function of dissipating electrostatic charges, and of giving some protection during its entire life. Thus, it is recommended, that the user establish an in-house test for electrical resistance, which is carried out at regular and frequent intervals.”

Perforation resistance

Additional information shall be given regarding perforation resistance: “The perforation resistance of this footwear has been measured in the laboratory using standardized nails and forces. Nails of smaller diameter and higher static or dynamic loads will increase the risk of perforation occurring. In such circumstances, additional preventative measures should be considered. Three generic types of perforation resistant inserts are currently available in PPE footwear. These are metal types and those from non-metal materials, which shall be chosen on basis of a job-related risk assessment. All types give protection against perforation risks, but each has different additional advantages or disadvantages including the following:

- **Metal (e.g. S1PS, S3):** Is less affected by the shape of the sharp object/hazard (i.e. diameter, geometry, sharpness) but due to shoemaking techniques may not cover the entire lower area of the foot.
- **Non-metal (PS or PL or category e.g. S1PS, S3L):** May be lighter, more flexible and provide greater coverage area, but the perforation resistance may vary more depending on the shape of the sharp object/hazard (i.e. diameter, geometry, sharpness). Two types in terms of the protection afforded are available. Type PS may offer more appropriate protection from smaller diameter objects than type PL.

Warranty & Returns

Returns and warranties are assessed on an individual basis. Our returns and warranty policy is available upon request.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Please consider recycling.

Dromex: Cornubia Ridge Logistics Park, 30 Umganu Road, Flanders, Blackburn, Durban, South Africa, 4319
T. +27(31) 713 1960 E. info@dromex.co.za www.dromex.co.za

Manufactured by: Ningbo Fastest Safety, Production Products Co., Ltd
 RM 803, No. 456 Middle Taikang Road, Yinzhou, Zhejiang, P. R. China

Disclaimer

Dromex reserves the right to make changes without further notice to any products herein to improve function, design or reliability and validity. Dromex does not assume any liability arising out of the application or use of any product described herein. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

Latest update: 23/10/2024