


Dromex



OIL-TECH GLOVE



DG-OIL-TECH-KW



Description

Dromex® OIL-TECH-KW seamless, double dipped and fully coated nitrile, knit wrist style gloves protects the hands against mechanical risks whilst providing exceptional grip.

With innovative nitrile micro foam technology on the palm, fingers and knuckles, this glove features the following:

- Superior dexterity.
- An enhanced grip in dry and wet applications, whilst providing resistance to oils, fats and grease.
- Strong tear resistant properties when hands are exposed to abrasion hazards.

The OIL-TECH -KW provides liquid and water resistance protection to the entire hand region (excluding knitted wrist region) and has a 13-gauge seamless nylon liner for comfort which is easy to put on and take off.

Dromex® OIL-TECH gloves are suitable for use in industries such as Oil and Gas Industry (OGP), mining and extraction, heavy machinery, aerospace, mechanical workshops, oil and grease environments, automotive and precision engineering applications.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

These gloves should not be worn where there is a risk of entanglement by moving parts of machines.

Do not expose gloves to contact with fire.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer.

The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

The levels of performance mentioned herein are obtained from the tests done according to conditions defined by the applicable standard.

Compliance & Conformity

- Complies with the requirements of CE type examinations EN 420:2003+A1:2009 for innocuousness, with a level 5 dexterity rating.
- Approved to EN 388:2016 + A1:2018 (4,1,2,1,X,) Protective gloves against mechanical risks.

Specifications

Style: 26cm (Size 10), coated nitrile glove with foam coated palm, fingers and knuckles

Liner: 13G nylon liner

Palm: 2mm

Back: 2mm

Cuff: 5cm, Knit wrist with a polyester binding

Mass: 100g Per pair (size 10)

Packaging, Storage & Obsolescence

Packed as an individual pair in 1 polybag. Store in a cool dry, that is clean and ventilated and place away from sunlight. Stored correctly, the gloves physical properties will not change for up to three years.

All gloves should be thoroughly inspected before use to ensure no damage is present. In case of deterioration (cuts, tear), the glove must be replaced immediately.



Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed however, should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands. The gloves may then be de-contaminated as indicated below.

We recommend that no bleaching or oxidising ingredients or any fabric softeners be used.

Recommended washing temperature is between 40°C and 60°C (104~140°F) with mild detergents.

Drying temperature should not exceed 70°C (158°F).

There is no remarkable impact on cut resistance during the normal life cycle of a glove however, depending on glove construction, staining and cleaning method, the differences in shrinkage, weight loss, yarn strength and colour may occur.

In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Due to a wide variety of possible constructions and combinations with other materials we recommend to always consult your professional cleaning service to determine the best suitable cleaning method.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Sizes Available


8-11

Code	Size	Palm Length	Glove Length-Min
DG-OIL-TECH-KW-8	S/M	95mm (±2mm)	240
DG-OIL-TECH-KW-9	M/L	100mm (±2mm)	250
DG-OIL-TECH-KW-10	L/XL	105mm (±2mm)	260
DG-OIL-TECH-KW-11	XL/XXL	110mm (±2mm)	270


** As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.*

** Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.*

Measurement Guide



Marking



Materials



1. Wing thumb
2. Nitrile foam coated palm & fingers
3. 5cm Knitted wrist

Dromex: Cornubia Ridge Logistics Park, 30 Umganu Road, Flanders, Blackburn, Durban, South Africa, 4319
T. +27(31) 713 1960 E. info@dromex.co.za www.dromex.co.za

Disclaimer

Dromex reserves the right to make changes without further notice to any products herein to improve function, design or reliability and validity. Dromex does not assume any liability arising out of the application or use of any product described herein. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

Latest update: 23/10/2024